المواصفات الفنية الخاصة بالمناقصة العامة رقم المناقصة: (٢٠١١/٤٩)

الخاصة بشراء وتوريد كاميرات مراقبة المؤسسة العامة للاتصالات السلكية واللاسلكية الإدارة العامة للمشتريات والمخازن إدارة المشتريات والمناقصات إدارة المشتريات – قسم العقود والمناقصات

PTC

IP Surveillance System Requirements (Mareb)

5-1

GENERAL

- Specification section covers the vender should be do testing supplying delivering to site erecting, connection up, testing, commissioning performance testing demonstrating and handing over in working order of the complete IP Surveillance System installation.
- IP Surveillance System equipment's and installation should be supplied and installed in all applicable standards.
- Drawings and general provisions of Contract, including General and special Conditions and Division of (General requirements), apply to work of this section.

DESCRIPTION OF WORKS

- Work should include providing all materials equipment, accessories, services and tests necessary to complete and make ready for operation.
- IP Surveillance system in accordance with Drawings and Specifications.

EQUIPMENT'S WARRANTY

- Guarantee equipment under these specifications against defective parts.
- Supplier should bring standard warranties for a period of not less than one year from the date of initial start-up.
- In addition to the need to Owner acceptance of the software and hardware, which
 will mentioned in the contract of working system and include labor and coming
 necessary repairs at the work site and when the need.
- IP Surveillance should be provided for the areas, as shown on the drawings.
- Contractor should be responsible for the final location of all the cameras giving optimum coverage of there are as to be surveyed.
- Contractor should be responsible for suitable bracket to fix cameras in their final locations.
- Final location, fixing methods, camera housing and color finishes should be subject to approval by the consultant Engineer.

PUBLIC TLECOMMUNICATION CORPORATION
Management Information system Department

CAMERAS

- The cameras should be of the solid state, charge coupled device (CCO) type and should be provide a minimum of Color mode automatically switched mode to black and white pictures.
- Tube cameras will not be accepted.

TECHNICAL SPECIFICATION

First: FIXED DOME INDOOR CAMERA IP IR.

Detail	Qty.
1/3"Scan CMOS	SELECTION OF STREET
Day and night function	
Minimum illumination 0 lux with IR LED on.	
18 fps at 1280 x 1024 resolutions.	
Connector Ethernet RJ 45.	
Power PoE Class 3 / DC 12V.	.3
IP address filtering	U
3GPP/ISMA	
Selectable H.264, MPEG-4SP, MJPEG compressions with dual streaming.	
Video motion detection.	
Digital input and digital output.	
16 languages on Web interface	

MOUNTING BRACKETS

Which should be insuring installation on ceilings.

TECHNICAL SPECIFICATION

Second: OUTDOOR POE BULLET CAMERA

Detail .	Qty.
• 1/3" Sony Super HAD interlaced scan CCD	
 Minimum illumination 0 lux with IR LED on 	
 Built-in 3.8-9.5 mm / F1.2 DC iris vari-focal lens 	
• 25/30 fps at full D1 resolution	
 Selectable MPEG-4 SP, MJPEG compressions 	4
Two-way audio	
Video motion detection	
 Analog video output with 540 TVL 	
Weatherproof IP66 rated casing	
 Powered by PoE Class 3 / DC 12V 	

| PUBLIC TLECOMMUNICATION CORPORATION Management Information system Department SANA'A

MOUNTING BRACKETS

Camera Bracket and Cover.

TECHNICAL SPECIFICATION

Third: OUTDOOR SPEED DOME CAMERA

Detail	Qty.
 1/4" Sony EXview HAD Interlaced Scan CCD 	
 Day and night function with mechanical IR cut filter 	
 Minimum illumination 0.01 lux at F1.4 	
18x optical zoom	
• 25/30 fps at full D1 resolution	1
MPEG-4 ASP compression	•
Video motion detection	
Digital input and digital output	
 Analog video output with 530 TVL 	
Weatherproof IP66 rated casing	

MOUNTING BRACKETS

· Camera Bracket and Cover.

GENERAL SPECIFICATIONS Lenses

- Built-in f3.3~12mm / F1.6 Megapixel vari-focal lens.
- Lenses should have a focal length selected by the contractor to give optimum coverage of the areas to be surveyed.
- Lenses should be exchanged during testing and corner missioning at no extra cost to the contract.

CONTROL AND MONITORING

Detail	Qty.
Processor: Intel Core 2 Duo, E8400 (3.0GHz, 1333MHz, 6MB).	
Memory: 2048MB (1x2048MB) 1066Mhz DDR3 Dual Channel.	
Hard Drive: 250GB (7200RPM) SAT A 3.5inch.	
Optical Drive: 16X DVD+/-RW Drive.	1
Security: Chassis Intrusion Switch.	•
Speakers: Internal Speaker.	
Keyboard: Arabic USB.	
Monitor: LCD 19".	

SWITCHING

PoE Switch.	1
Network Data Transfer Rate: 10/100 Mbps (24 Ports).	- 1

1200

SERVER

Items	Detail	Qty.
Name	Brand	BOT WITH BEAUTIFUL TO A PARTY OF THE STATE O
Туре	Rack	
Processor Cache Memory	One Xeon Quad-core (3.16Ghz) L2 8 MB cache memory	
RAM	8 GB DDR3	
NIC	10/100/1000 NIC	1
HDD	1 Terabyte SAS 15K Hot Swap Hard driv	
RAID Controller	support RAID 0 and RAID 1	
Optical Drive	DVD Combo	
Monitor	17" LCD Monitor	200
Software	Windows 2008 server	
Warranty	One Year	

SOFTWARE

Dami	Qty.
Support for multiple sites surveillance.	
Support H.264/MPEG-4/MJPEG formats up to Megapixel resolution.	
Support 1, 4, 6, 8, 9, 10, 16, 25, 36, 49, 64 window layout.	
PTZ and speed control, preset points and tours, mouse PTZ.	
E-maps with camera icons and mini live views.	
Scheduled, event triggered and manual recording.	1
Time and event based search.	
Full screen playback with AVI video export function.	
4-channel synchronized playback.	
Event management with motion detection and DI/DO.	
Two-way audio, multi-channel audio broadcast.	
Unlimited number of remote clients using web.	

PUBLIC TLECOMMUNICATION CORPORATION
Management Information system Department

SANA'A

مشروع نظام الرقابة المرئية بالكاميرات لفرع مأرب جدول المتطلبات

N	Item	Qty	Unit Price	Total Price
1	FIXED DOME INDOOR CAMERA IP IR	3		
2	OUTDOOR POE BULLET CAMERA	4		
3	OUTDOOR SPEED DOME CAMERA	1		
3	CONTROL AND MONITORING	1		
4	SWITCHING	1		
5	SERVER	1		
6	SOFTWARE	1		
7	INSTALLATION	1		
	TOTAL			

مع التزام الشركة : - بالتركيب والتشغيل للمنظومة مع توريد جميع الملحقات والكابلات اللازمة لتركيب وتشغيل المنظومة .